



movemanSKG

Prestige A401

Freestanding Platform Lift

Prestige A401 Advantages

Our Companion Prestige A401 is a belt driven platform lift. Quiet, smooth and easy to operate it fits easily into any built environment.

Aesthetically pleasing, the Prestige A401 can travel up to 13 meters, carry a load of 400kg, and has a generous platform area of 1.5 x 1.1 metres.

The Prestige A401 is fully compliant with the European Machinery Directive and all UK and Ireland Building Regulations, the requirements of Document M and the Disability Discrimination Act.

The Prestige A401 belt drive system means the self supporting enclosure can be glazed on all four sides. Numerous colours and finishes are available and the carriage control console can be customised in brass, stainless steel or hardwoods such as oak and mahogany.

The Prestige A401 operates quietly and economically, making it suitable for historic and listed buildings open to the public. It has a small footprint and shallow pit requirement, yet generous platform size, meaning in appropriate situations it can be installed where a conventional lift is not possible.

The Prestige A401 comes with many refinements for ultimate passenger comfort and safety including ergonomic controls, level indicators, door safety systems and battery lowering in case of power supply interruption.



Prestige A401 Data

| | |
|-----------------------|---|
| Drive | Belt drive with variable frequency motor |
| Load | 400kg |
| Travel | 13 metres |
| Headroom | 2.3 metres |
| Platform size | 1.5m long x 1.1m wide (Minimum 1.4m x 1.1m Part M) |
| Configuration | Single Entry, Open Through or Adjacent |
| Speed | 0.15 metres per sec |
| Footprint | 1.65m long X 1.35m wide (pit and floor cut-out) |
| Pit | 50mm deep or a ramp will be supplied |
| Controls | Vandal resistant tactile illuminated push buttons - constant pressure operation to comply with codes |
| Communication | Visual & voice annunciation of floor reached Hands free intercom on carriage |
| Supply voltage | 240v, single phase, 50 Hz 20 amp |
| Duty cycle | 15 return cycles per hour |
| Doors | 2m high x 0.9m wide single swing with self closer |
| Shaft | Prefabricated insulated modules |
| Finishes | PVC laminated steel in a choice of colours Stainless steel option |
| Lighting | Recessed downlighters set in shaft ceiling |
| Flooring | Anti slip rubber flooring |
| Safety | Alarm on carriage with battery back-up Battery lowering in case of power failure Sensitive edges around full perimeter of carriage Fully electrically and mechanically interlocked doors |
| Options | Extensive range of additional features available |



movemanSKG (a trading division of Otis Limited), 123 Abbey Lane, Leicester. LE4 5QX.
Tel: 0116 225 2100, Fax: 0116 261 0397 Web: www.movemanskg.co.uk