

# primas



Platform Lift



## Description

Small and compact in appearance, the Prima is designed for use where a small change in level inhibits the less able and wheelchair users. The Prima will accommodate a small change in floor levels up to a height of 550mm. It has a closed platform height of only 30mm and requires no pit. The standard unit has a mechanically and electrically interlocked upper landing gate and an automatic hinged platform ramp for lower level access. The Prima is suitable for internal and external applications. It is a compact product that requires very little space and blends easily with its surroundings. Its platform incorporates a shallow ramp for easy entry and exit. The safety gate at the upper level locks automatically and ensures user safety.

## Key Features:

Shallow ramp for ease of access. Ramp automatically folds-up when lift is operated.

The lift is battery powered so limited use is possible in the event of a power failure.

Robust powder coated finish, colour creamy white 10B15

The Prima can be installed internally or externally

## Data:

Drive	Electro-hydraulic
Capacity	225kg
Upper level gate	Manual swing interlocked gate - handed to suit
Maximum travel	550mm
Speed	25mm/sec
Access Ramp	Automatically rises to retain wheelchair on platform
Ramp Gradient	1:8
Platform closed height	30mm
Platform width	750mm
Platform length	1220 mm
External width	980 mm
External length (incl. gate)	1300 mm
External length (ramp lowered)	1515 mm
Side frame height	700 mm
Handrail height	810 mm
Platform Controls	Light touch 'hold-to-run' plus emergency lowering - left or right hand to choice
Remote controls	Call stations at both upper and lower levels
Power supply	240v 50Hz 1ph (13 amp fused isolator)
Operating voltage	24v DC via battery (able to be used in the event of power supply failure)
Battery box	225mm high x 225mm long x 75mm deep
Distance from battery to lift	5.5m max
Duty cycle	5 return cycles per hour
Finish	Platform in aluminium - remainder powder coated steel 'Magnolia' 10B15
Environment	Internal or external application



**movemanSKG (a trading division of Otis Ltd)**

**123 Abbey Lane, Leicester LE4 5QX.**

**Telephone: 0116 225 2100**

**Fax: 0116 261 0397**

**email: sales@movemanskg.co.uk**

**Website: www.movemanskg.co.uk**