

# THE COMPANION EXTREME

## External Wheelchair Access Lift

The Companion Extreme is manufactured in Sweden and has been designed for the harsh external environment encountered during the Scandinavian winters. The Extreme enables wheelchair users or less able people to gain access to buildings or changes in levels of up to 2 metres high. Safety being paramount, the key safety features are gate interlocks at the upper landing and on the platform along with handrails plus a safety trip bar and a pressure sensitive plate under the platform. The lift has been designed to be simple to use and for speed of installation.

### KEY FEATURES:

- Designed for harsh external environments.
- Genuinely free standing.
- Minimal builders work & only 1 day to install.
- Complies with all current British & European Legislation.
- CE marked.
- 3 service visits included in the first 12 months.

### OPTION AVAILABLE:

- RAL colour of your choice
- Galvanised
- Glazed (Polycarbonate) gates and handrail.
- Landing call station posts
- Key isolation
- 240v Single phase powered
- Adjacent entry



### TECHNICAL DATA:

Environment:	External
Drive:	Screw & Nut
Load:	300kg
Travel:	Up to 2000mm
Platform Size:	910mm wide x 1400mm long
External Dimensions:	1270mm wide x 1510mm long
Base required:	1400mm wide x 1550mm long
Entry Configuration:	Through as standard
Mast handing:	Left or right side
Speed:	0.06 m/s
Supply Voltage:	415v 3 phase 20A
Control voltage:	24 v
Power Pack:	Integral
Duty cycle:	20 Cycles per hour
Landing gate – steel infilled:	910mm wide x 1100mm high
Platform gate – railed:	910mm wide x 1100mm high
Finish:	Grey spray painted finish RAL 7039
Access onto the lift:	60mm high Access Ramp
Maximum weight of the lift fully loaded:	800kg

